



PLAQUES ET VIS GROS FRAGMENT 4,5 / 6,5 MM

PLATES AND SCREWS LARGE FRAGMENT 4.5 / 6.5 MM

VIS SPONGIEUSE

CANCELLOUS SCREW

VIS SPONGIEUSE

CANCELLOUS SCREW



Matériau : inox ISO 5832-1

Material : stainless steel ISO 5832-1

Vis spongieuse ø 6,5 mm Filetage court 16 mm	Vis spongieuse ø 6,5 mm Filetage long 32 mm	Vis spongieuse ø 6,5 mm Filetage total	Longueur
Cancellous screw 6.5mm dia. 16mm short thread	Cancellous screw 6.5mm dia. 32mm long thread	Cancellous screw 6.5mm dia. full thread	Length
		NQANNZZ65025	25 mm
NQALNZZ65030		NQANNZZ65030	30 mm
NQALNZZ65035		NQANNZZ65035	35 mm
NQALNZZ65040	NQAMNZZ65040	NQANNZZ65040	40 mm
NQALNZZ65045	NQAMNZZ65045	NQANNZZ65045	45 mm
NQALNZZ65050	NQAMNZZ65050	NQANNZZ65050	50 mm
NQALNZZ65055	NQAMNZZ65055	NQANNZZ65055	55 mm
NQALNZZ65060	NQAMNZZ65060	NQANNZZ65060	60 mm
NQALNZZ65065	NQAMNZZ65065	NQANNZZ65065	65 mm
NQALNZZ65070	NQAMNZZ65070	NQANNZZ65070	70 mm
NQALNZZ65075	NQAMNZZ65075	NQANNZZ65075	75 mm
NQALNZZ65080	NQAMNZZ65080	NQANNZZ65080	80 mm
NQALNZZ65085	NQAMNZZ65085	NQANNZZ65085	85 mm
NQALNZZ65090	NQAMNZZ65090	NQANNZZ65090	90 mm
NQALNZZ65095	NQAMNZZ65095	NQANNZZ65095	95 mm
NQALNZZ65100	NQAMNZZ65100	NQANNZZ65100	100 mm
NQALNZZ65105	NQAMNZZ65105	NQANNZZ65105	105 mm
NQALNZZ65110	NQAMNZZ65110	NQANNZZ65110	110 mm
NQALNZZ65115	NQAMNZZ65115	NQANNZZ65115	115 mm

Diamètre du filetage / Thread dia. : 6.5 mm

Diamètre du noyau / Core dia. : 3.0 mm

Diamètre de la tige / Shaft dia. : 4.5 mm

Diamètre de la tête / Head dia. : 8.0 mm

Empreinte hexagonale / Hexagonal print : 3.5 mm

Mèche du trou fileté / Drill bit for threaded hole : 3.2 mm

Mèche pour tige / Drill bit for shaft : 4.5 mm

