



PLAQUES ET VIS PETIT FRAGMENT 3,5 / 4,0 MM

PLATES AND SCREWS SMALL FRAGMENT 3.5 / 4.0 MM

VIS SPONGIEUSE

CANCELLOUS SCREW

VIS SPONGIEUSE

CANCELLOUS SCREW



Matériau : inox ISO 5832-1

Material : stainless steel ISO 5832-1

Vis spongieuses ø 3,5mm	Vis spongieuses ø 4,0mm / filetage court	Vis spongieuses ø 4,0mm / filetage total	Longueur
Cancellous screws 3.5mm dia.	Cancellous screws 4.0mm dia. /short thread	Cancellous screws 4.0mm dia. / full thread	Length
NQANNZZ35010	NQALNZZ40010	NQANNZZ40010	10 mm
NQANNZZ35012	NQALNZZ40012	NQANNZZ40012	12 mm
NQANNZZ35014	NQALNZZ40014	NQANNZZ40014	14 mm
NQANNZZ35016	NQALNZZ40016	NQANNZZ40016	16 mm
NQANNZZ35018	NQALNZZ40018	NQANNZZ40018	18 mm
NQANNZZ35020	NQALNZZ40020	NQANNZZ40020	20 mm
NQANNZZ35022	NQALNZZ40022	NQANNZZ40022	22 mm
NQANNZZ35024	NQALNZZ40024	NQANNZZ40024	24 mm
NQANNZZ35026	NQALNZZ40026	NQANNZZ40026	26 mm
NQANNZZ35028	NQALNZZ40028	NQANNZZ40028	28 mm
NQANNZZ35030	NQALNZZ40030	NQANNZZ40030	30 mm
NQANNZZ35032		NQANNZZ40032	32 mm
		NQANNZZ40034	34 mm
	NQALNZZ40035		35 mm
NQANNZZ35036		NQANNZZ40036	36 mm
		NQANNZZ40038	38 mm
NQANNZZ35040	NQALNZZ40040	NQANNZZ40040	40 mm
		NQANNZZ40042	42 mm
		NQANNZZ40044	44 mm
NQANNZZ35045	NQALNZZ40045		45 mm
		NQANNZZ40046	46 mm
		NQANNZZ40048	48 mm
NQANNZZ35050	NQALNZZ40050	NQANNZZ40050	50 mm
		NQANNZZ40052	52 mm
		NQANNZZ40054	54 mm
		NQANNZZ40056	56 mm
NQANNZZ35055			55 mm
		NQANNZZ40058	58 mm
NQANNZZ35060		NQANNZZ40060	60 mm

Diamètre du filetage / Thread dia. : 3.5 mm / 4.0 mm

Diamètre du noyau / Core dia. : 2.4 mm / 1.9 mm

Diamètre de la tige / Shaft dia. : 2.3 mm

Diamètre de la tête / Head dia. : 6.0 mm

Empreinte hexagonale / Hexagonal print : 2.5 mm

Mèche du trou fileté / Drill bit for threaded hole : 2.5 mm

Mèche pour tige / Drill bit for shaft : 3.5 mm

